

FOCUS

Quarterly E-Magazine of the Institute of Quantity Surveyors, Sri Lanka Volume 16: Issue 01, January 2023



Published by: Institute of Quantity Surveyors Sri Lanka (IQSSL)

Waste Minimisation?

Construction Specialised Mobile Apps for Effective Project Implementation

Recent Memories



Disclaimer

The information contained in this publication should not form the basis of any decision as to a particular course of action; nor should it be relied upon as a professional advice. Under no circumstances shall the publisher be liable for any direct, incidental, special and consequential loss and damage that results from the readers' reliance or non-reliance of information provided in this publication. The copyright of this publication vests solely and exclusively with the publisher and no part may be reproduced or transmitted by any process or means without prior written permission of the Institute of Quantity Surveyors, Sri Lanka.



Seasonal Greeting from IQSSL	3
Message from the President	4
Message from the Secretary	5
Can Buildings Be Green Without Waste Minimisation?	6
Recent CPDs	9
APC Application and 2023 Schedule	10
IQS Estimating Guide	11
Construction Specialised Mobile Apps for Effective Project Implementation	28
New Associate Members - 2022	33
Recent Memories	34
IQSSL Membership Subscription Form	39





Message from the President

Ch.QS. Prof (Mrs.) Kanchana Perera

BSc (Hons) QS, MPhil, FIQSSL, FAIQS, FRICS, CQS, ICECA President - Institute of Quantity Surveyors, Sri Lanka

I am very pleased to send this message to 'Focus' publishing at the dawn of the New Year 2023. Year 2022 was a very challenging year, since Sri Lanka was in the midst of a grave economic crisis. The economic crisis has badly affected the construction sector, which is considered a of barometer the economy. As construction professionals, we are all undoubtedly undergoing a difficult time and facing huge challenges as a prominent industry in the country. As we are stepping into the New Year 2023, we need to develop a systematic process of defining goals to overcome the economic maladies and steps that need to be taken to achieve such goals for the betterment of construction industry and our profession.

Being professionals, we cannot afford to give up our professions at this stage just because the times have become tough for no fault on our part...

We need to be courageous, positive, and look for practical solutions to the problems we face. I strongly believe that as quantity surveyors, we can explore solutions to the prevailing crisis. The Institute of Quantity Surveyors Sri Lanka (IQSSL), being the regulating body of the Quantity Surveying profession in Sri Lanka, had already taken steps towards achieving such goals by participating in with discussions the relevant government authorities and informing of observations our suggestions in numerous occasions. Thus, we fervently hope that in this New Year we will be able to develop a good strategic plan to manage the problems in the construction industry and the country.

I wish the members of IQSSL and their families a very happy, healthy and a prosperous New Year 2023.





Message from the Secretary

Ch.QS. Tilanka Wijesinghe

BSc (Hons) QS, PG. Dip in Project Mgt, FIQSSL Secretary - Institute of Quantity Surveyors, Sri Lanka

It is with great pleasure that I write this message on the dawn of year 2023.

All of us negotiated the year 2022 despite the unprecedented challenges inflicted by the financial crisis of the country. We are up against another challenging year ahead.

It is only a positive mind set and courage that can drive us during the year 2023 toward individual success and the rebuilding of the nation. The crisis could give us a window of opportunity to realise our true potential through creativity.

I am confident that the IQSSL and its members owing to the capabilities and perseverance, can fit well into the challenging task ahead of us.

I wish all IQSSL members, stockholders, and the general public the courage and perseverance they will need to succeed in 2023.





Research Article

Can Buildings Be Green Without Waste Minimisation?

Panchali Weerakoon and Tharusha Ranadewa

Department of Building Economics, University of Moratuwa

Introduction

The construction industry has been identified as one of the most profitable industries which has become more complex with the improvements of modern technology (Alaloul et al., 2021). Even though the construction industry has many positive impacts in terms of a country's economy (Gnanothayan & Kauškale, 2022), it has been accused for being environmental inimical due to the traditional construction methods used in the industry (Du et al., 2021). Therefore, the demand towards sustainable developments have impacted the construction industry in major to promote sustainable practices (Opoku & Fortune, 2011). Through practicing, it can bring various objectives such as responsibility towards environment, social awareness and economic profitability towards the built environment as well as for the wider community to accomplish the ultimate sustainability goals (Ali & Al Nsairat, 2009).

A Green Rating system generally monitor the sustainable performance of a construction throughout the life cycle of the project in terms of many aspects such as; energy efficiency, water efficiency, material efficiency, indoor environmental quality enhancement, waste reduction as well as operations and maintenance optimization (Illankoon et al., 2017; Shan & Hwang, 2018). Thus, this paper focuses to investigate the relationship waste minimisation through green rating systems in Sri Lankan construction industry.

Construction Waste Management

Rapid development of construction technology, global economy, urbanisation, and establishment of fourth industrial revolution has caused

increasing of the living standard of societies all over the world (Chummun, 2019). Simultaneously, waste generation has amplified rapidly over past years and waste is predicted to increase by 300% in the year 2100 (Cohen et al., 2015). This has adversely affected on overall performance of construction projects, the society and the nature (Etipola et al., 2021). Construction and demolition (C&D) waste is generally a mixture of additional materials produced during a construction project or the waste generated through a demolition activity of a constructed facility (Chowdhury et al., 2016). Even though many researches has conducted researches in the area of construction waste management in Sri Lanka (Rameezdeen et al., 2004), still it is being treated as one of the major issues in the Sri Lankan construction industry (Dinu et al., 2022). According to the research carried out by Jayawardane (1994) noted that, wastage of concrete and mortar respectively takes up to 21% and 25% in Sri Lankan construction sites. In 2004, Rameezdeen et al. (2004) quantified the material wastage in Sri Lankan construction sites as follows;

Material	Wastage (%)
Sand	25%
Lime waste	20%
Cement waste	14%
Brick waste	14%
Ceramic tile waste	10%
Timber waste	10 %

(Rameezdeen et al., 2004)

Rameezdeen et al., (2004) indicated that material handling processes and improper management are the major causes for waste generation.



In general, C & D waste is bulky, heavy and is mostly unsuitable for disposal by incineration composting. Therefore, managing construction waste specifically in urban areas (Sfk & Ding, 2007). 50% of the waste generated through construction activities use to landfills as a disposal method which is acknowledged worldwide Iskandarani, 2012). The research carried out by Nagapan et al. (2012) noted that about 13-26% of wastes collected for landfills are waste materials related to construction works.


Landfill sites act as ecological reactors where wastes undergo physical, chemical and biological transformations which might be harmful to the environment (Nanda & Berruti, 2021). To overcome environmental problems such as, construction and demolition waste, CO2 emission, energy consumption and raw material extraction in built environment (Schützenhofer et al., 2022), it is vital to practice sustainable construction methods (Lima et al., 2021) with the aid of an acceptable green rating system.

Green Rating Systems

Green Rating system is a method which is used as an action strategy in order to associate construction projects (Cao et al., 2015).

An increased focus and attention on the development of sustainable buildings has led to the certification of various green buildings during the last three decades (Olawumi et al., 2020). Several green building certification systems (GBCSs) such as Building Research Establishment Environmental Assessment Method (BREEAM), Leadership in Energy and Environmental Design (LEED) has established as well-known green rating systems globally (Tleuken et al., 2021).

In the Sri Lankan context, GREEN SL rating system was introduced by Green Building Council of Sri Lanka in 2011(District & Scott, 2009). These rating tools has been developed based on geographical conditions (Ding, 2008). Therefore, the focus is different from each other when comparing these rating tools. Soharu et al. (2021) stated that achievable points without waste minimization in BREEAM, LEED rating systems are respectively 81%, 88% which leads to achieve a higher grading in both rating systems. Further Soharu et al. (2021) indicated that through waste minimization, the maximum points percentage which can be gained from these rating systems are 20%, 12% accordingly.





This confirms that even without focusing on waste minimization, projects can be labelled as green buildings. In GREEN SL rating system out of total 100 points, 84% can be achieved without any consideration about minimizing waste and classified the building as Platinum certified green building (GBCSL, 2022). In Sri Lankan context, GREEN SL rating system does not provide adequate guideline of waste minimization or solution to overcome the problem of disposing bulk construction waste in to lands or using construction waste to land fill. According to the pilot case studies carried out it was evident that GREEN SL rating system accepts landfill as a waste disposal method which will be harmful for the human well-being.

Conclusion and Recommendation

Sustainable building construction captures all integrated parameters towards the environment, social, and economic (Soharu et al., 2021b). The available green rating systems do not facilitate construction waste minimization in an effective manner. Even though there are mandatory points available for waste minimization in green rating systems, it is not adequate enough to solve the prevailing problems related to construction waste. Hence, it is recommended to incorporate mandatory points for waste minimization through the process of construction and use of 3R concept (Reduce, Reuse, Recycle) in construction. Further, new concepts such as, Circular Economy, Nature Based Solutions and Close-loop supply chain management can be incorporated as mandatory points in the Green rating systems to minimize the construction waste.

References

Al-Hajj, & Iskandarani. (2012). Reducing Waste Generation on the UAE Construction Sites. 7th International Conference on Innovation in Architecture, August 2012.

- Alaloul, W. S., Musarat, M. A., Liew, M. S., Qureshi, A. H., & Maqsoom, A. (2021). Investigating the impact of inflation on labour wages in Construction Industry of Malaysia. *Ain Shams Engineering Journal*, 12(2), 1575–1582.
 - https://doi.org/10.1016/j.asej.2020.08.036
- Ali, H. H., & Al Nsairat, S. F. (2009). Developing a green building assessment tool for developing countries Case of Jordan. *Building and Environment, 44*(5), 1053–1064. https://doi.org/10.1016/J.BUILDENV.2008.07.015
- Chowdhury, F. H., Raihan, M. T., Islam, G. M. S., & Ramiz, F. (2016). Construction Waste Management Practice: Bangladesh Perception. 3rd International Conference on Advances in Civil Engineering (ICACE 2016), Chittagong, Bangladesh, October 2016, 289–294.
- Chummun, B. Z. (2019). Environmental Performance in the Waste Management Industry of Africa. November, 278–305. https://doi.org/10.4018/978-1-5225-7638-9.ch011
- Ding, G. K. C. (2008). Sustainable construction—The role of environmental assessment tools. *Journal of Environmental Management*, 86(3), 451–464. https://doi.org/10.1016/J.JENVMAN.2006.12.025
- Dinu, W., Chanaka, A., & Dahanayake, R. (2022). THE APPLICABILITY OF REGULATIONS FOR THE DISPOSAL OF CONSTRUCTION. June, 821–832.
- District, C., & Scott, R. (2009). S Ocial & E Conomic F Actors. June, 4–5.
- Du, Q., Wu, J., Cai, C., Li, Y., Zhou, J., & Yan, Y. (2021). Carbon mitigation by the construction industry in China: a perspective of efficiency and costs. *Environmental Science and Pollution Research*, 28(1), 314–325. https://doi.org/10.1007/s11356-020-10412-z
- GBCSL. (2022). GREEN SL ® RATING SYSTEM FOR NEW CONSTRUCTIONS.
- Gnanothayan, J. G., & Kauškale, L. (2022). Development of the Construction Industry and Its Interconnection with the Development of National Economy of Sri Lanka. Baltic Journal of Real Estate Economics and Construction Management, 10(1), 106–112. https://doi.org/10.2478/bjreecm-2022-0007
- Illankoon, I. M. C. S., Tam, V. W. Y., Le, K. N., & Shen, L. (2017). Key credit criteria among international green building rating tools. *Journal of Cleaner Production*, 164, 209–220. https://doi.org/10.1016/j.jclepro.2017.06.206



- Jayawardane, A. K. . (1994). Are we aware of the extent of wastage on our building construction sites? *Engineer, 20*(2), 41–45.
- Lima, L., Trindade, E., Alencar, L., Alencar, M., & Silva, L. (2021). Sustainability in the construction industry: A systematic review of the literature. *Journal of Cleaner Production*, 289, 125730. https://doi.org/10.1016/J.JCLEPRO.2020.125730
- Nagapan, S., Rahman, I. A., Asmi, A., Memon, A. H., & Latif, I. (2012). Issues on construction waste: The need for sustainable waste management. *CHUSER* 2012 2012 IEEE Colloquium on Humanities, Science and Engineering Research, December, 325–330. https://doi.org/10.1109/CHUSER.2012.6504333
- Nanda, S., & Berruti, F. (2021). Municipal solid waste management and landfilling technologies: a review. *Environmental Chemistry Letters, 19*(2), 1433–1456. https://doi.org/10.1007/s10311-020-01100-y.
- Olawumi, T. O., Chan, D. W. M., Chan, A. P. C., & Wong, J. K. W. (2020). Development of a building sustainability assessment method (BSAM) for developing countries in sub-Saharan Africa. *Journal of Cleaner Production*, 263, 121514. https://doi.org/10.1016/J.JCLEPRO.2020.121514.
- Opoku, A., & Fortune, C. (2011). The implementation of sustainable practices through leadership in construction organizations. Association of Researchers in Construction Management, ARCOM 2011 Proceedings of the 27th Annual Conference, 2(September), 1145–1154.

- Rameezdeen, R., Kulatunga, U., & Amaratunga, & D. (2004). Quantification of Construction Material Waste in Sri Lankan Sites. *International Built and Human Environment Research Week, 1992,* 1-9.
- Sfk, E., & Ding, J. (2007). Construction and Demolition Waste Management: Current Practices in Asia Related papers Reuse of municipal const ruct ion wast es as aggregat es in concret e Sohaib Naseer T WENT Y-EIGHT NAT IONAL CONVENT ION OF CIVIL ENGINEERS AND NAT ONAL SEMINAR ON Role.
 - https://www.researchgate.net/publication/26820 6184
- Shan, M., & Hwang, B. (2018). Green building rating systems: Global reviews of practices and research efforts. *Sustainable Cities and Society*, *39*, 172–180. https://doi.org/10.1016/j.scs.2018.02.034
- Soharu, A., Naveen, B. P., & Sil, A. (2021a). Effectiveness of existing green rating systems towards zero waste construction. *AIP Conference Proceedings*, 2396(October). https://doi.org/10.1063/5.0066416
- Soharu, A., Naveen, B. P., & Sil, A. (2021b). Effectiveness of existing green rating systems towards zero waste construction. *AIP Conference Proceedings*, 2396(September). https://doi.org/10.1063/5.0066416
- Tleuken, A., Tokazhanov, G., Guney, M., Turkyilmaz, A., & Karaca, F. (2021). Readiness Assessment of Green Building Certification Systems for Residential Buildings during Pandemics. https://doi.org/10.3390/su13.

Recent CPDs

S/N	CPD No.	Date	Title	Resource Person	Abstract
1	CPD 1 - 2022/23	25 th November 2022	Moving to and succeeding in the Middle East: essential elements	Ch.QS S.P.A. Keerthiratna, BSc (QS) Hons, MBA, AIQSSL, MRICS, Expert QS, Hon. Co-Representative of IQSSL in Dubai, UAE. Ch.QS. M.B. Ekanayake, BSc (QS) Hons, AIQSSL. MRICS, MCI(Arb), Arbitrator, Expert in Construction Claims and Dispute Resolution.	IQSSL presented this CPD to share knowledge of Middle East practitioners with QSs who seek opportunities and career progression in the region.
2	CPD 2 - 2022/23	6 th December 2022	Decarbonising Challenge: Are we ready?	Prof. Shiromi Karunaratne, BSc (Eng) Hons, PhD, MIESL, CEng, (Professor at Department of Civil Engineering, Sri Lanka Institute of Information Technology)	IQSSL presented this CPD webinar to discuss the decarbonising challenges associated with the construction sector and present methods available to assess the same.



APC Application and 2023 Schedule

IQSSL hereby wishes to call for applications for the Assessment of Professional Competence (APC) for the March 2023 session. The APC registration will commence on 6th January 2023 and will close on 27th January 2023. The candidates who are working abroad are eligible to sit for the APC through online mode and the candidates who are working in Sri Lanka shall sit for the APC through the regular physical mode. (This however may be subjected change.)

Eligible candidates shall submit duly filled applications either to the IQSSL Secretariat at the OPA Building or via e-mail to iqssl@sltnet.lk, before 3.00 p.m. on 27th January 2023. Please refer below schedule for more details. All the necessary forms are available to be downloaded from www.iqssl.lk.

Registration fees (for the APC application and Charter Classes) can be deposited to the following bank account and the remittance slips shall be attached to the registration form.

Name of Account: Institute of Quantity Surveyors Sri Lanka

Account Number: 1208409001


Bank Name and Branch: Commercial Bank - Borella

Currency Type: LKR.

For any further clarifications, please e-mail to iqssl@sltnet.lk or contact Harshani on 0774441221.

No	Description	Date	Remarks
	Registration and Submissions		
1	Commencement of registration	January 6, 2023	
2	Deadline for registration	3:00 PM, January 27, 2023	Online submission of the application form and payment proof shall be as a single PDF.
3	Deadline for diary submission	3:00 PM, February 03, 2023	Overseas candidates can submit the diaries via the web link provided by IQSSL after registration. Candidates in Sri Lanka shall submit the diaries to the IQSSL Secretariat.
4	Issuing of APC Practice Problem	10:00 AM, February 17, 2023	
5	APC report submission	3:00 PM, February 21, 2023	Overseas candidates can submit the report via the web link provided by IQSSL. Candidates in Sri Lanka shall submit the
	Charter Classes		report to the IQSSL Secretariat.
6	Commencement of Registration for charter classes	January 6, 2023	Charter classes will be held online
7	Commencement of Charter Classes	January 22, 2023	Classes will be held on Sundays. The class schedule will be published in due course.
8	End of Charter Classes	February 12, 2023	
	APC Viva Voce		
9	APC Interview Day 01	March 11, 2023	Subject to change
10	APC Interview Day 02	March 12, 2023	
11	APC Interview Day 03	March 18, 2023	Subject to change
12	APC Interview Day 04	March 19, 2023	
	Reserve Date	March 26, 2023	Subject to change

IQS ESTIMATING GUIDE



2023



IQS Estimating Guide

Foreword

We are in an era where construction activities are influenced by evolving technologies and business psychologies. Since the first official release of Building Schedule of Rates (BSR) in 1989 construction inputs, methods and industry characteristics have evolved to a greater extent, necessitating an appropriate new publication with revised norms for rate analysis. The absence of a suitable estimating guide has been a concern felt by the stakeholders in the construction industry.

Considering this need of the industry and the requests made by many personnel and institutions in the construction industry, Institute of Quantity Surveyors, Sri Lanka (IQSSL) has initiated the process of developing an IQS Estimating Guide (IQSEG). Main objective of this process was to develop IQSEG for pricing and rate analysis for work items most commonly used and which have high contribution to cost in building construction.

The name "Guide" is used as this provides a guide for user to make necessary adjustments in the rate analysis based on the nature, location, method and complexity of the project, so that the misconception that the published rates can be applied to every situation is eliminated.

With the involvement of experienced panel of professional Quantity Surveyors an initial draft was finalized. In order to validate the applicability of IQSEG to the current industry practices, the norms were verified with selected major contracting and consulting organization.

As the first landmark of this process a sample form of Section 'F – Concrete' is published, expecting feedback for its further development. IQSEG is in the progress and other sections including preambles for the Masonry, Concrete, Waterproofing, Metal & Woodwork, Roofing, Finishes and paint work and will be issued as an interim version for feedback in future.

Feedback on this sample form for further improvements is appreciated on behalf of IQSSL in developing the IQSEG with added work sections in future.

Estimating Guide Development Committee IQSSL



Guidance Notes for Concrete Work

General

- 1. Work items considered under this section include concrete, formwork, reinforcement and pre-cast concrete elements.
- 2. Norms given are only for the listed inputs in the rate Build Up and the other inputs required for particular; operational systems, method, location and situation are to be decided and included by the user. Refer to "Inclusions and Exclusions" below for further details.
- 3. All the norms are given for unit rate pricing unless noted otherwise.
- 4. Norms include a normative percentage for inherent material wastages as indicated in each "Rate Build Up sheet". Users may adjust these percentages based on corresponding waste control management systems.
- 5. Given norms are for work done at ground level unless noted otherwise. Users shall make necessary adjustments for the additional labour and/or material without duplicating pricing or prices in the Preliminaries Bill to suit the level or altitude at which the work is to be constructed.
- 6. Refer to the "Applicable Table/s" given at the end of the Rate Build Up sheet in this Section for additional information.

Measurement

- 1. Measurements shall be made in accordance with the applicable SMM, Preambles to BOQ and the dimensions given on the drawings, specifications and other available documents or as specified.
- 2. Rate Build Ups are prepared on the basis that the measurements are made of the net actual quantity of each item for the purpose of valuations. Any other adjustments for; wastage, bulking, shrinkage, sundries, voids/intersections not deducted, coverage rules under the SMM, Preambles to BOQ and these guidance notes that are required, shall be decided and included by the user.
- 3. Thicknesses specified in the documents shall be the finished thickness.



Material, Labour and Plant

- 1. The given norms apply to the mixing of concrete using ordinary Portland cement according to the mix designs as given in "Applicable Table/s".
- 2. Ready-mix concrete used shall conform to relevant specifications.
- 3. No separate allowance is made in the norms for the supply of ready-mix concrete for transporting, admixtures, handling, pumping, hoisting and placing at any height or depth.
- 4. Sand to be river sand, mined sand or manufactured sand as per the relevant specifications.
- 5. Water used shall be as per the relevant specifications.
- 6. Labour norms given are for manual mixing/placing and using machinery as noted in the Rate Build Up Sheet for relevant concrete items.

Mixing and Placing of In-Situ Concrete

- 1. Rates shall include for the supply of materials, mixing, hoisting/lowering, placing in position, packing and tamping around reinforcements including vibration and curing of Concrete elements using necessary 'standard' material. equipment, labour and plant for Site mixed concrete.
- 2. All concrete mix designs are to be suitable for the purpose for which they are intended and in accordance with relevant specifications and standards.
- 3. The norms given include the labour required for curing of concrete using water.
- 4. It is assumed that the water required for curing has been included elsewhere.
- 5. Compaction is considered to be by hand and / or by mechanical vibration.
- 6. Norms for plain concrete blinding beds exclude any formwork to the edges.

Inclusions and Exclusions

1. This Estimating Guide provides norms for the work executed under 'standard' conditions only, and the cost impact on the particular work items due to the following variable factors are excluded in the norms given. User shall make necessary allowances in his calculations according to the actual requirements as applicable (next page):



- Operation related costs
- Location related costs
- Method related costs
- Items identified to be measured separately in the applicable SMM
- Lump sum items
- Items separately identified in the Preliminaries
- Rectification work
- Costs incurred in complying with the Conditions of Contract
- Items cost of which are covered in the overheads
- Design where expressly required
- Transportation of materials to site and on site
- Falls, cambers and shaped profiles.

Precast Concrete (Lintel)

- 1. Norms exclude the following. User shall make necessary allowances in the rate for the same as per the actual requirement:
 - i. Casting with all necessary concrete, formwork, and reinforcement including forming pockets for lifting hooks and the like and filling of such pockets as specified;
 - ii. Loading, unloading, transporting to and in site, handling and stacking;
 - iii. Hoisting to any height or depth, erecting and fixing in position (except labour for same) building in, including bedding and jointing in mortar/concrete as required and necessary strutting and temporary supports; and
 - iv. Complying with applicable specifications, conditions or Preambles to BOQ.



F1 Rate Build-up Sheet

INSTITUTE OF QUANTITY SURVEYORS SRI LANKA

Exclusions

Mixing Method

Placing Method

ESTIMATING GUIDE

RATE BUILD-UP SHEET 001 **BREAKDOWN REFERENCE -G15 MIXING ONLY** / F1.010 **RATE APPLICATION GUIDES AND CRITERIA** WORK SECTION : F1 Insitu Concrete SPECIFICATION : Chapter 04 Guide Criterion PHRASEOLOGY REF. TYPICAL DESCRIPTION FOR BILLS OF QUATITIES: Input norms are considered for Allowed Wastage Factor Mixing only of Concrete in Grade 15 : 5% average wastage for materials : 1. Placing of concrete 2. Admixtures 3. Preliminaries 4. Tansport (General and specific)

Cost	Cost Description		with was	stage) and Rates	Rate Analysis			Net
Code			Unit	Rate	Labour	Material	Plant/tools	Unit Rate
	Materials							
	[Assumed mix 1:3:6 (40mm)]							
	Cement (50kg)	15.00	bags					
	Sand	0.60	m³					
	Metal (40mm)	1.05	m³					
	Labour							
	Mixer operator	1.00	day					
	Unskilled labour	6.00	day					
	Plant							
	Concrete mixer 0.3m3/0.2m3	2.50	hrs					
	Tools Small tools		ltem					
	Sundries		ltem					
	Add: Project specific inputs							
Total A	mount (Excl. VAT)	3.00	m ³					
Mixing describ	only of concrete in G15 as ed	1.00	m ³					

: Mechanical (Site mixture)

: N/A

Applicable Table/s : Table No -Applicable Sketch/s Sketch No -(Will be provided later)

REFERENCE

Method of Measurements : SLS 573: 1999 Method of Measuremets of Building Works (First Revision)

Specification : Specifications for Building Works - Volume I, 3rd Edition (Revised) July 2004 (SCA/4/I)

Pricing Preambles : Section 01 - Concrete Works

Preliminaries : ICTAD/ID/04: Guidelines for Preparation of Bill No.1 - Preliminaries for Building Works

(2nd Edition - June 2009) and Preliminary Bill in the particular Bills of Quantities



002

BREAKDOWN REFERENCE - G20 MIXING ONLY

/ F1.020

RATE APPLICATION GUIDES AND CRITERIA

Guide

Criterion

WORK SECTION : F1 Insitu Concrete

SPECIFICATION : Chapter 04

PHRASEOLOGY REF. :

Input norms are considered for : 3m3

Allowed Wastage Factor : 5% average wastage for materials

Exclusions

: 1. Placing of concrete
2. Admixtures

3. Preliminaries

4. Tansport (General and specific)

Mixing Method : Mechanical (Site mixture)

Placing Method : N/A

TYPICAL DESCRIPTION FOR BILLS OF QUATITIES : Mixing only of Concrete in Grade 20

ific)

Cost	Cost		ith wast	age) and Rates		Rate Analysis		Net
Code	Description	Qty	Unit	Rate	Labour	Material	Plant/tools	Unit Rate
	Materials							
	[Assumed mix 1:2:4 (40mm)]							
	Cement (50kg)	20.00	bags					
	Sand	0.60	m ³					
	Metal (40mm)	0.95	m³					
	Labour							
	Mixer operator	1.00	day					
	Unskilled labour	6.00	day					
	Plant							
	Concrete mixer 0.3m3/0.2m3	3.00	hrs					
	Tools							
	Small tools		Item					
	Sundries		Item					
	Add: Project specific inputs							
Total Ar	nount (Excl. VAT)	3.00	m ³					
Mixing describe	only of concrete in G20 as	1.00	m³					

Applicable Table/s : Table No (Will be provided later)

Applicable Sketch/s : Sketch No - N/A

REFERENCE

Method of Measurements : SLS 573: 1999 Method of Measuremets of Building Works (First Revision)

Specification : Specifications for Building Works - Volume I, 3rd Edition (Revised) July 2004 (SCA/4/I)

Pricing Preambles : Section 01 - Concrete Works

Preliminaries : ICTAD/ID/04: Guidelines for Preparation of Bill No.1 - Preliminaries for Building Works

(2nd Edition - June 2009) and Preliminary Bill in the particular Bills of Quantities



BREAKDOWN REFERENCE - G25 MIXING ONLY / F1.030

RATE APPLICATION GUIDES AND CRITERIA WORK SECTION : F1 Insitu Concrete SPECIFICATION : Chapter 04 Guide Criterion PHRASEOLOGY REF.

Input norms are considered for : 3m3

Allowed Wastage Factor : 5% average wastage for materials

Exclusions : 1. Placing of concrete

> 2. Admixtures 3. Preliminaries

3.00

1.00 m

4. Tansport (General and specific)

m³

Mixing Method : Mechanical (Site mixture

Placing Method : N/A

Description

[Assumed mix 1:1.5:3 (20mm)] Cement (50kg)

Concrete mixer 0.3m3/0.2m3

Add: Project specific inputs

Cost

Code

Materials

Sand

Labour

Tools Small tools

Sundries

Total Amount (Excl. VAT)

Mixing only of concrete in G25 as

Metal (20mm)

Mixer operator

Unskilled labour

Mechanica N/A	al (Site n	nixture)					
Inputs (with was	stage) and Rates		Rate Analysis		Net	
Qty	Unit	Rate	Labour	Material	Plant/tools	Unit Rate	
26.00	bags						
0.50	m³						
0.92	m³						
1.00	day						
7.00	day						
4.50	hrs						
4.50	1113						
	Item						
	Item						

TYPICAL DESCRIPTION FOR BILLS OF QUATITIES:

Mixing only of Concrete in Grade 25

Applicable Table/s : Table No Applicable Sketch/s (Will be provided later)

REFERENCE

described

Method of Measurements : SLS 573: 1999 Method of Measuremets of Building Works (First Revision)

Specification : Specifications for Building Works - Volume I, 3rd Edition (Revised) July 2004 (SCA/4/I)

Pricing Preambles : Section 01 - Concrete Works

: ICTAD/ID/04: Guidelines for Preparation of Bill No.1 - Preliminaries for Building Works **Preliminaries**

(2nd Edition - June 2009) and Preliminary Bill in the particular Bills of Quantities



004

BREAKDOWN REFERENCE - 50mm SCREED GRADE 15

/ F1.040

RATE APPLICATION GU	IDES AND CRITERIA	WORK SECTION	: F1 Insitu Concrete
Guide	Critorian	SPECIFICATION	: Chapter 04
Guide	Criterion	PHRASEOLOGY REF.	:

Input norms are considered for : 10m²

Allowed Wastage Factor

Exclusions

: 5% average wastage for materials: 1. Mixing of concrete

2. Preparation of ground to receive concrete

3. Expansion joints4. Damp proof membrane5. Construction joints

6. Formwork7. Preliminaries8. Tansport (General and specific)

Mixing Method : N/A
Placing Method : Manual

TYPICAL DESCRIPTION FOR BILLS OF QUATITIES:

Placing only of 50mm thick mass concrete in G15 for screed in foundation, poured into ground.

Cost	B	Inputs (ts (with wastage) and Rates		Rate Analysis			Net
Code	Description	Qty	Unit	Rate	Labour	Material	Plant/tools	Unit Rate
	Materials							
	Site mixed concrete in G15	0.55	m³					
	Labour							
	Mason	0.30	day					
	Unskilled labour	0.60	day					
	Tools							
	Small tools		Item					
	Sundries		Item					
	Add: Project specific inputs							
Total An	nount (Excl. VAT)	10.00	m²					
_	only of 50mm thick mass e in G15 as described	1.00	m ²					

Applicable Table/s
: Table No (Will be provided later)

Applicable Sketch/s
: FOOTINGS
Sketch No (Will be provided later)

REFERENCE

Method of Measurements

: SLS 573: 1999 Method of Measuremets of Building Works (First Revision)

Specification : Specifications for Building Works - Volume I, 3rd Edition (Revised) July 2004 (SCA/4/I)

Pricing Preambles : Section 01 - Concrete Works

Preliminaries : ICTAD/ID/04: Guidelines for Preparation of Bill No.1 - Preliminaries for Building Works

(2nd Edition - June 2009) and Preliminary Bill in the particular Bills of Quantities



005

BREAKDOWN REFERENCE - COLUMN BASE GRADE 25

/ F1.050

RATE APPLICATION	GUIDES AND CRITERIA	WORK SECTION	: F1 Insitu Concrete
Guide	Criterion	SPECIFICATION	: Chapter 04 and 05
Guide		PHRASEOLOGY REF.	:

Input norms are considered for : 1m3 (5nrs)

Allowed Wastage Factor : 5% average wastage for materials

Exclusions

: 1. Mixing of concrete

2. Expansion joints (If required)

3. Bonding agents

4. Formwork5. Preliminaries

6. Tansport (General and specific)

7. Provision for services

Mixing Method : N/A
Placing Method : Manual

TYPICAL DESCRIPTION FOR BILLS OF QUATITIES:

Placing only of reinforced concrete in G25 for column base in foundation, poured into formwork.

Inputs (with wastage) and Rates Rate Analysis Cost Description Code Labour Material Plant/tools **Unit Rate** Qty Site mixed concrete in G25 1.05 m^3 Jute hessian (2 time use) 2.50 Labour 0.25 day Unskilled labour 0.66 day Vibrator operator 0.25 day Carpenter 0.25 day Unskilled labour(Curing) 0.10 day Plant Vibrator (Electrical) 0.07 hrs Tools Small tools Item Sundries Item Add: Project specific inputs Total Amount (Excl. VAT) 1.00 m^3 Placing only of concrete in G25 in

Applicable Table/s

REFERENCE Method of Measurements

column base as described

: SLS 573: 1999 Method of Measuremets of Building Works (First Revision)

Specification : Specification

: Specifications for Building Works - Volume I, 3rd Edition (Revised) July 2004 (SCA/4/I)

Pricing Preambles : Section 01 - Concrete Works

1.00

Table No

(Will be provided later)

 m^3

Preliminaries

: ICTAD/ID/04: Guidelines for Preparation of Bill No.1 - Preliminaries for Building Works (2nd Edition - June 2009) and Preliminary Bill in the particular Bills of Quantities

Applicable Sketch/s

Sketch No -

(Will be provided later)



006

BREAKDOWN REFERENCE - COLUMNS UP TO GFL GRADE 25 / F1.060

RATE APPLICATION GUIDES AND CRITERIA WORK SECTION : F1 Insitu Concrete : Chapter 04 and 05 SPECIFICATION Guide Criterion PHRASEOLOGY REF. TYPICAL DESCRIPTION FOR BILLS OF QUATITIES: Input norms are considered for : 1m3 (10nrs) Allowed Wastage Factor Placing only of reinforced concrete in G25 : 5% average wastage for materials Exclusions : 1. Mixing of concrete for isolated square shaped columns 2. Bonding agents (If required) sectional area less than 0.10m2 3. Formwork - Up to Ground floor level 4. Preliminaries 5. Tansport (General and specific) 6. Provision for services Mixing Method

Cost		Inputs (with was	stage) and Rates	Rate Analysis		Net	
Code	Description	Qty	Unit	Rate	Labour	Material	Plant/tools	Unit Rate
	Materials							
	Site mixed concrete in G25 Jute hessian (2 time use)	1.05 13.20	m³ m⁴	12,500.00				
	Labour							
	Mason	0.50	day	2,250.00				
	Unskilled labour	1.60	day	1,750.00				
	Vibrator operator	0.50	day	2,250.00				
	Carpenter	0.50	day	2,250.00				
	Unskilled labour(Curing)	0.10	day	1,750.00				
	Plant							
	Vibrator (Electrical)	0.20	hrs	200.00				
	Tools							
	Small tools		Item					
	Sundries		Item					
	Add: Project specific inputs							
Total Ar	nount (Excl. VAT)	1.00	m ³					
_	only of concrete in G25 in s as described	1.00	m³					

Applicable Table/s
: Table No (Will be provided later)

Applicable Sketch/s
: FOOTINGS
Sketch No (Will be provided later)

REFERENCE

Placing Method

Method of Measurements :

: SLS 573: 1999 Method of Measuremets of Building Works (First Revision)

Specification

: Specifications for Building Works - Volume I, 3rd Edition (Revised) July 2004 (SCA/4/I)

Pricing Preambles : Section 01 - Concrete Works

: Manual

Preliminaries

: ICTAD/ID/04: Guidelines for Preparation of Bill No.1 - Preliminaries for Building Works (2nd Edition - June 2009) and Preliminary Bill in the particular Bills of Quantities



007

BREAKDOWN REFERENCE - SLAB ON GRADE, GRADE G20 / F1.070

RATE APPLICATION GUIDES AND CRITERIA WORK SECTION : F1 Insitu Concrete SPECIFICATION : Chapter 04 and 05 Guide Criterion PHRASEOLOGY REF. TYPICAL DESCRIPTION FOR BILLS OF QUATITIES: Input norms are considered for : 1m3 Allowed Wastage Factor Placing only of reinforced concrete in G20 : 5% average wastage for materials Exclusions for beds and slabs on ground, thickness : 1. Mixing of concrete 2. Bonding agents (If required) less than 150mm 3. Expansion joints 4. Compressible filler 5. Formwork (If required) 6. Preliminaries 7. Tansport (General and specific) 8. Provision for services Mixing Method : N/A Placing Method : Manual

Cost	Cost		with was	tage) and Rates		Rate Analysis		Net
Code	Description	Qty	Unit	Rate	Labour	Material	Plant/tools	Unit Rate
	Materials							
	Site mixed concrete in G20	1.05	m³					
	Jute hessian (2 time use)	10.00	m ²					
	Labour							
	Mason	0.20	day					
	Unskilled labour	0.60	day					
	Carpenter	0.20	day					
	Unskilled labour(Curing)	0.10	day					
	Tools							
	Small tools		Item					
	Sundries		Item					
	Add: Project specific inputs							
otal Ar	nount (Excl. VAT)	1.00	m ³		-	-		
_	only of concrete in G20 in slab e as described	1.00	m³					

Applicable Table/s
: Table No (Will be provided later)

Applicable Sketch/s
: Ground floor slab details
Sketch No (Will be provided later)

REFERENCE

Method of Measurements : SLS 573: 1999 Method of Measuremets of Building Works (First Revision)

Specification : Specifications for Building Works - Volume I, 3rd Edition (Revised) July 2004 (SCA/4/I)

Pricing Preambles : Section 01 - Concrete Works

Preliminaries : ICTAD/ID/04: Guidelines for Preparation of Bill No.1 - Preliminaries for Building Works

(2nd Edition - June 2009) and Preliminary Bill in the particular Bills of Quantities



800

BREAKDOWN REFERENCE - COLUMNS GF TO FF GRADE 25 / F1.080

RATE APPLICATION GUIDES AND CRITERIA **WORK SECTION** : F1 Insitu Concrete SPECIFICATION : Chapter 04 and 05 Guide Criterion PHRASEOLOGY REF. TYPICAL DESCRIPTION FOR BILLS OF QUATITIES: Input norms are considered for : 1.5m3 (5nrs) Allowed Wastage Factor : 5% average wastage for materials

Exclusions : 1. Mixing of concrete 2. Bonding agents (If required)

6. Provision for services

3. Formwork 4. Preliminaries

5. Tansport (General and specific)

Mixing Method : N/A Placing Method : Manual

Cost

Code

Placing only of reinforced concrete in **G25** for attached square shaped columns sectional area less than 0.10m2 - From Ground floor to First floor level

Inputs (with wastage) and Rates Rate Analysis Net Description Unit Labour Material Plant/tools **Unit Rate** Qty Rate Site mixed concrete in G25 1.58

 m^3 Jute hessian (2 time use) 20.00 abour 0.80 Mason day Unskilled labour 3.15 dav Vibrator operator 0.80 day 0.80 Carpenter day Unskilled labour(Curing) 0.20 day Vibrator (Electrical) 0.30 hrs Tools Small tools Item Sundries Item Add: Project specific inputs Total Amount (Excl. VAT) 1.50 m^3 Placing only of concrete in G25 in 1.00 m^3

Applicable Table/s Applicable Sketch/s : Table No (Will be provided later) Sketch No -(Will be provided later)

REFERENCE

columns as described

Method of Measurements : SLS 573: 1999 Method of Measuremets of Building Works (First Revision)

Specification : Specifications for Building Works - Volume I, 3rd Edition (Revised) July 2004 (SCA/4/I)

Pricing Preambles : Section 01 - Concrete Works

: ICTAD/ID/04: Guidelines for Preparation of Bill No.1 - Preliminaries for Building Works **Preliminaries**

(2nd Edition - June 2009) and Preliminary Bill in the particular Bills of Quantities



RATE BUILD-UP SHEET 009 BREAKDOWN REFERENCE -**FIRST FLOOR SLAB GRADE 25** F1.090 RATE APPLICATION GUIDES AND CRITERIA WORK SECTION : F1 Insitu Concrete SPECIFICATION : Chapter 04 and 05 Criterion PHRASEOLOGY REF. : TYPICAL DESCRIPTION FOR BILLS OF QUATITIES: Input norms are considered for : 1.5m3 Allowed Wastage Factor : 10% average wastage for materials Placing only of reinforced concrete in G25 Exclusions for suspended slabs, thickness less than : 1. Mixing of concrete 2. Bonding agents (If required) 150mm 3. Expansion joints - In First floor level 4. Compressible filler 5. Formwork (If required) 6. Preliminaries 7. Tansport (General and specific) 8. Provision for services N/A Mixing Method

Cost	B	Inputs (with wastage) and Rates			Rate Analysis			Net
Code	Description	Qty	Unit	Rate	Labour	Material	Plant/tools	Unit Rate
	Materials							
	Site mixed concrete in G25	1.65	m³					
	Jute hessian (2 time use)	12.00	m^2					
	Labour							
	Mason	0.75	day					
	Unskilled labour	2.75	day					
	Vibrator operator	0.75	day					
	Carpenter	0.75	day					
	Unskilled labour(Curing)	0.20	day					
	Plant							
	Vibrator (Electrical)	0.11	hrs					
	Tools							
	Small tools		Item					
	Sundries		Item					
	Add: Project specific inputs							
otal Ar	nount (Excl. VAT)	1.50	m ³					
	only of concrete in G25 in slab	1.00	m³					
as desci	ribed	Table No			Applicable SI	vetch/s ·	Slah details	

Applicable Table/s : Table No -Applicable Sketch/s Slab details (Will be provided later) Sketch No -

REFERENCE

Placing Method

Method of Measurements : SLS 573: 1999 Method of Measuremets of Building Works (First Revision)

Manual

Specification : Specifications for Building Works - Volume I, 3rd Edition (Revised) July 2004 (SCA/4/I)

Pricing Preambles : Section 01 - Concrete Works

: ICTAD/ID/04: Guidelines for Preparation of Bill No.1 - Preliminaries for Building Works **Preliminaries** (2nd Edition - June 2009) and Preliminary Bill in the particular Bills of Quantities



010

BREAKDOWN REFERENCE - STAIRS GF TO FF GRADE 25 / F1.100

RATE APPLICATION GUIDES AND CRITERIA WORK SECTION : F1 Insitu Concrete SPECIFICATION : Chapter 04 and 05 Guide Criterion PHRASEOLOGY REF. TYPICAL DESCRIPTION FOR BILLS OF QUATITIES: Input norms are considered for : 1.5m3 Allowed Wastage Factor Placing only of reinforced concrete in G25 : 5% average wastage for materials Exclusions for stairs, steps and waist : 1. Mixing of concrete 2. Bonding agents (If required) - From Ground floor to First floor level 3. Formwork 4. Preliminaries 5. Tansport (General and specific) 6. Provision for services Mixing Method : N/A Placing Method : Manual

Cost Description Inputs (with wastage) and Rates Rate Analysis			Net					
Code	Description	Qty	Unit	Rate	Labour	Material	Plant/tools	Unit Rate
	Materials							
	Site mixed concrete in G25	1.58	m³					
	Jute hessian (2 time use)	9.00	m ²					
	Labour							
	Mason	0.65	day					
	Unskilled labour	1.50	day					
	Vibrator operator	0.65	day					
	Carpenter	0.65	day					
	Unskilled labour(Curing)	0.20	day					
	Plant							
	Vibrator (Electrical)	0.11	hrs					
	Tools							
	Small tools		Item					
	Sundries		Item					
	Add: Project specific inputs							
Total Ar	mount (Excl. VAT)	1.50	m³					
Placing as desci	only of concrete in G25 in stairs ribed	1.00	m³					
Applica	pplicable Table/s : Table No -				Applicable SI	ketch/s :	Staircase details	5

REFERENCE

Method of Measurements : SLS 573: 1999 Method of Measuremets of Building Works (First Revision)

(Will be provided later)

Specification : Specifications for Building Works - Volume I, 3rd Edition (Revised) July 2004 (SCA/4/I)

Pricing Preambles : Section 01 - Concrete Works

Preliminaries : ICTAD/ID/04: Guidelines for Preparation of Bill No.1 - Preliminaries for Building Works

(2nd Edition - June 2009) and Preliminary Bill in the particular Bills of Quantities

Sketch No -(Will be provided later)



011

BREAKDOWN REFERENCE - BEAMS IN FF GRADE 30A

/F1.110

Net

RATE APPLICATION GUI	WORK SECTION	: F1 Insitu Concrete	
Guide	Criterion	SPECIFICATION	: Chapter 04 and 05
Guide		PHRASEOLOGY REF.	:

Input norms are considered for : 1.5m3

Allowed Wastage Factor : 5% average wastage for materials

Exclusions : 1. Mixing of concrete

2. Bonding agents (If required)

3. Preliminaries

4. Tansport [General and specific (If any excluding pump car)]

5. Provision for services

Inputs (with wastage) and Rates

Mixing Method : Readymixed delivered to Site
Placing Method : By Pump car + Labour

Description

TYPICAL DESCRIPTION FOR BILLS OF QUATITIES:
Placing only of reinforced concrete in
G30A for attached beams, sectional area
more than 0.10m2
- In First floor level

Rate Analysis
Labour Material Plant/tools

Code	Description	Qty	Unit	Rate	Labour	Material	Plant/tools	Unit Rate
	Materials							
	Readymixed concrete in G30A	1.58	m³					
	Jute hessian (2 time use)	6.50	m ²					
	Labour							
	Mason	0.80	day					
	Unskilled labour	3.15	day					
	Vibrator operator	0.80	day					
	Carpenter	0.80	day					
	Unskilled labour(Curing)	0.20	day					
	Plant							
	Vibrator (Electrical)	0.11	hrs					
	Pump car	1.58	m³					
	Tools							
	Small tools		Item					
	Sundries		Item					
	Add: Project specific inputs							
Total Ar	mount (Excl. VAT)	1.50	m ³					
	only of concrete in G30A in ed beams as described	1.00	m³					
Applica	Applicable Table/s :				Applicable S	ketch/s	: Beam details	
		(Will be pro	ovided lat	er)			Sketch No -	
					ll .		(Will be provide	d later)
								-

REFERENCE

Cost

Method of Measurements : SLS 573: 1999 Method of Measuremets of Building Works (First Revision)

Specification : Specifications for Building Works - Volume I, 3rd Edition (Revised) July 2004 (SCA/4/I)

Pricing Preambles : Section 01 - Concrete Works

Preliminaries : ICTAD/ID/04: Guidelines for Preparation of Bill No.1 - Preliminaries for Building Works (2nd Edition - June 2009) and Preliminary Bill in the particular Bills of Quantities



012

BREAKDOWN REFERENCE - 225x150mm PRECAST LINTELS /F1.120 **IN FF GRADE 25**

RATE APPLICATION GUIDES AND CRITERIA **WORK SECTION** : F1 Insitu Concrete SPECIFICATION : Chapter 04 and 05 Guide Criterion PHRASEOLOGY REF. TYPICAL DESCRIPTION FOR BILLS OF QUATITIES: Input norms are considered for : 4500mm (1 nr) Allowed Wastage Factor Size 225x150mm pre-cast lintels in Grade : N/A Exclusions : 1. Surface preparation 25 concrete, length exceeding 3.0m but 2. Preliminaries not exceeding 6.0m. Rate shall include for

3. Tansport (General and specific)

stirrups at 150mm centers. - In Ground floor level

necessary formwork and T10-4nrs and R6

Mixing Method : Delivered to Site

Placing Method : Manual

Cost	Biti	Inputs (with wastage) and Rates Rate Analysis			Net			
Code	Description	Qty	Unit	Rate	Labour	Material	Plant/tools	Unit Rate
	Materials							
	Pre-cast lintels	1.00	nr					
	Labour							
	Mason	0.50	day					
	Unskilled labour	1.00	day					
	Tools							
	Small tools		Item					
	Sundries		Item					
	Add: Project specific inputs							
Total Ar	nount (Excl. VAT)	1.00	nr		-	-		
Pre-cast	t lintels in G25 as described	1.00	nr					

Applicable Table/s	: Table No -	Applicable Sketch/s	: Lintel details
	(Will be provided later)	ll l	Sketch No -
		ll l	(Will be provided later)
		ll l	

REFERENCE

Method of Measurements : SLS 573: 1999 Method of Measuremets of Building Works (First Revision)

: Specifications for Building Works - Volume I, 3rd Edition (Revised) July 2004 (SCA/4/I) Specification

Pricing Preambles : Section 01 - Concrete Works

Preliminaries : ICTAD/ID/04: Guidelines for Preparation of Bill No.1 - Preliminaries for Building Works (2nd Edition - June 2009) and Preliminary Bill in the particular Bills of Quantities



Research Article

Construction Specialised Mobile Apps for Effective Project Implementation

Dulshan Costa and Menaha Thayaparan

Department of Building Economics, University of Moratuwa

Introduction

Construction industry is complex а and the challenging industry, which involves coordination of many different activities and stakeholders to complete a project on time and within budget (Newman, et al., 2021). Construction 4.0 refers to the application of advanced technologies to the construction industry. It involves the use of robotics, automation, artificial intelligence, and other digital technologies to improve efficiency, productivity, and safety on construction sites. This is part of a broader trend known as Industry 4.0, which refers to the fourth industrial revolution, characterized by the integration of advanced technologies into other industries. Construction 4.0 is expected to lead to significant improvements in the construction industry, including reduced costs and improved project outcomes. A considerable amount of mobile apps are used in the construction industry

Construction Specialised Mobile Apps

A construction specialized app is a mobile application that is specifically designed for a particular aspect of the construction industry. These apps are typically used by construction professionals, such as architects, engineers, project managers, and contractors, to help them perform their jobs more efficiently and effectively (Ekow & Kofi, 2016). Construction specialized apps may focus on a specific aspect of the

construction process, such as project management, estimating, design, or material and equipment tracking. They may also provide access to specialized information and tools, such as construction codes and standards, or provide tools for collaboration and communication within a construction team. Construction specialized apps can help improve productivity, efficiency, and accuracy in the construction industry (PlanGrid Build | The #1 Construction App for Project Management, 2021). There are three main categories of construction specialised mobile apps as detailed below.

Project management apps: Provide tools and features that help construction managers to plan, schedule, and track projects. Allows including features such as project schedules, task lists, and progress tracking.

Estimating apps: Help contractors and project managers to estimate project costs and manage budgets. Facilitate to include features such as cost databases, cost calculators, and bid management tools (Procore Construction Management Software, 2021).

Design and modelling apps: Assist architects and engineers to design and model buildings and other structures. Features such as 3D modelling, rendering, and visualization tools are included (Construction & Floor Plan App For Contractors | magicplan, 2021).



Communication and collaboration apps: Allow construction professionals to communicate and collaborate with team members and clients. Messaging, file sharing, and project management tools are included to the App (PlanGrid Build | The #1 Construction App for Project Management, 2021).

Construction reference apps: These apps provide access to important construction industry information, such as codes and standards. They can include features such as searchable databases and offline access to reference materials.

Leading Construction Specialised Apps and Features

There are variety construction specialized apps available, and the leading apps may vary depending on the specific needs and preferences of users. However, some popular construction specialized apps and their features are identified in Table 1.

Accordingly, PlanGrid, AutoCAD 360, BIMx, MagicPlan, ARki and Procore are identified as most popular construction specialised apps in the construction industry. It was noted that, the state-of-the-art tech-based mobile applications allow the construction project to reduce the unnecessary wastes and complete the project within the given budget. This was further proven by many researchers, stating that the less human intervention reduces the unnecessary wastes in the construction project. Following section discusses the applications of recognised apps in construction projects.

Applications of Recognized Construction Specialised Apps in Construction Projects

Recognised Construction specialized apps can be applied in many different ways to improve efficiency, productivity, and safety on construction projects. The Table 2 represents the areas of recognised constructions apps that can be used in construction projects.

Table 1: Applications of Construction Apps

	PlanGrid	AutoCAD	BiMx	MagicPla	ARki	Procore
Project management	✓	✓	✓	✓	✓	✓
Design and modelling	✓	✓	✓	✓	✓	
Communication and collaboration	✓	✓	✓	✓	✓	✓
Access to construction industry information	✓	✓	*	×	×	×
Presentations and demonstrations	×	×	✓	×	✓	×
Estimating and budgeting	×	×	×	✓		✓
Quality and safety assurance	×	×	×	×	×	✓

Sources: (PlanGrid Build | The #1 Construction App for Project Management, 2021), (A360 | Project Collaboration in the Cloud, 2021), (BIMx, 2021), (Construction & Floor Plan App For Contractors | magicplan, 2021), (Augmented Reality platform for Architecture, Engineering and Construction, 2021), (Procore Construction Management Software, 2021). (Newman, et al., 2021)



Table 1: Construction Specialised Apps and Features

	App	Functions and Features
1	PlanGrid	PlanGrid is an advanced mobile application that fulfils the requirements in construction management.
		Features:
		✓ Automatically reads sheet names, descriptions and hyperlinks in drawings.
		✓ Annotation facility for PDF drawings.
		✓ Cloud-server security for data.
		✓ Blueprint adjustment facility for variation orders.
		✓ Present photo archive for progress photos and pinned directly onto construction blueprints.
		 Ability to share the latest plans, progress photos, markups with the entire project team.
		✓ End-to-end RFI (Request For Information) solution.
		✓ Report generation.
2	AutoCAD 360	AutoCAD 360 is a design application to draw, edit, and view two-dimensional (2D) Computer Aided Drawings (CAD) across multiple devices based on a web mobile application using cloud storage.
3	BIMx	BIMx is a Building Information Modelling based mobile application that allows users to navigate within drawing sheets and three dimensional (3D) building models.
		Features:
		✓ Photorealistic model of the 3D model.
		✓ Ability to trace 2D drawings in 3D.
		✓ Ability to access any building component which has BIM information.
		✓ Gravity and egress recognition mode.
		✓ Ability to give location feedback during navigation.
4	MagicPlan	MagicPlan is a state-of-the-art tech-based mobile application that uses inputs from the smartphone device such as camera, gyroscope, and laser distance meters to design complete floor plans automatically in 2D or 3D form within few seconds.



		 Features: ✓ Allowing the user to measure and sketch interior plans in 2D and 3D form using state-of-the-art tech with an easy-to-use user interface. ✓ Facilitate adding photos, 3600 images, custom forms, markups, and notes to create structured reports. ✓ Ability to automatically calculate pricing by combining take-off and estimate.
5)	ARki	ARki is an Android mobile application that allows users to visualize 3D building model files realistically by using Augmented Reality (AR) technology on site. Features: ✓ The offline storage model allows the user to store models on a native device to access them without an internet connection. ✓ Ability to import 3D building models in different formats such as SketchUp, ArchiCAD, Revit, and other 3D formats. ✓ Ability to visualise models on any scale using AR.
6	Procore	Procore is an Android application that allows users to access project documents, project details, schedules, and other construction sensitive information and automatically synchronise them in real-time when the device is connected to the internet. Features: ✓ Allows the user to view and revise drawings. ✓ Allows tracking on daily logs related to labour, communication, equipment, materials, and job site events. ✓ Allows to capture progress photos and link them to project drawings by location. ✓ Allows creating, editing, and sharing schedules.

Sources: (PlanGrid Build | The #1 Construction App for Project Management, 2021), (A360 | Project Collaboration in the Cloud, 2021), (BIMx, 2021), (Construction & Floor Plan App For Contractors | magicplan, 2021), (Augmented Reality platform for Architecture, Engineering and Construction, 2021), (Procore Construction Management Software, 2021). (Newman, et al., 2021)



Conclusion

The construction industry is constantly evolving, and the future is likely to bring many changes and advancements. Some potential developments in the construction industry include the use of more advanced technology to improve efficiency and reduce waste. The future of the construction industry is likely to be marked by continued innovation and a focus on improving efficiency and sustainability.

Construction apps can be very useful for a variety of reasons. For one, they can help construction workers and project managers to stay organized and manage their projects more efficiently. This can lead to increased productivity and a construction smoother overall process. Additionally, construction apps can help to improve communication among team members, making it easier to share information and collaborate on tasks. This can help to reduce the likelihood of errors and miscommunications, which can save time and money. It can provide access to a wide range of useful tools and resources, such as project management software, estimating tools, and safety guidelines. This can help workers to make more informed decisions and complete their tasks more effectively.

References

A360 | Project Collaboration in the Cloud. (2021, July 13). Retrieved from A360.autodesk.com: https://a360.autodesk.com/

Augmented Reality platform for Architecture, Engineering and Construction. (2021, July 13). Retrieved from DARF DESIGN: https://www.darfdesign.com/arki.html

BIMx. (2021, July 13). Retrieved from Graphisoft: https://graphisoft.com/solutions/bimx

Construction & Floor Plan App For Contractors | magicplan. (2021, July 13). Retrieved from Magicplan.app: https://www.magicplan.app/

Ekow, Y., & Kofi, O. (2016). Awareness and Utilization of Construction Related Smart Mobile Device Applications in the Construction Industry. *Science and Technology, 6*(1), 1-7. doi:10.5923/j.scit.20160601.01

Newman, C., Edwards, D., Martek, I., Lai, J., Rillie, I., & Thwala, W. (2021). Industry 4.0 deployment in the construction industry: a bibliometric literature review and UK-based case study. *Smart and Sustainable Built Environment, 10*(4), 557-580. doi:https://doi.org/10.1108/SASBE-02-2020-0016

PlanGrid Build | The #1 Construction App for Project Management. (2021, July 13). Retrieved from construction.autodesk.com:

https://construction.autodesk.com/products/autodesk-plangrid-build/

Procore Construction Management Software. (2021). Retrieved from Procore.com: https://www.procore.com/en-sg



New Associate Members - 2022



Mr. A.G.J. Roshan



Mr. G.D. Dhanitha



Mr. M.D. Wijesinghe



Mr. P.P. Ratnapala



Mr. W.C.A. Kumara



Mr. A.W.V. Udayanga



Mr. H.L.N.R. Perera



Mr. M.D.D.M. Sumathipala



Mr. S. Sivakumaran



Ms. C.J. Munaweera



Mr. D.D.J.A. Amarasena



Mr. K.D. Ruwan



Mr. P. Kirusanth




Mr. T.D. Wickramasekara



Ms. S. Thivya





Signing the Reciprocity with Royal Institution of Chartered Surveyors (RICS)

When:

September 2022 during the PAQS Visit



Recent Memories



When:

23rd to 25th September 2022



When:

4th and 5th November 2022





Recent Memories



What:


IQSSL Fundraising Event - Car Wash at Narahenpita

When:





Recent Memories



What:

AGM of IQSSL College of Quantity Surveying

When:

17th December 2022

Membership Subscription

<u>Dear Members</u>



If you haven't paid the subscription yet, please make arrangement to pay as soon as possible.

Our es	Our established payment methods are as follows; 1 Direct Deposits Account Name : INSTITUTE OF QUANTITY SURVEYORS SRI LANKA. Bank Name & Branch : Commercial Bank – Borella. Bank A/C No. : 1208409001					
2.	Bank Draft / TT Account Name Swift Code Bank Address	: INSTITUTE OF QUANTITY SURVEYORS SRI LANKA. : CCEYLKLX : Commercial Bank of Ceylon PLC. # 21, Bristol Street Colombo -01. Sri Lanka.				
3.	Credit Card	: At the IQSSL Office or by filling the detachable slip below, Visa and Master card only				
4.	Cash	: At the IQSSL Office				
Please send the original bank deposited slip to the Institute by registered post in order to update our records. If you have any further queries, please do not hesitate to contact Ms Piyumi on +94112595570 or e mail iqssl@sltnet.lk With well wishes, Institute of Quantity Surveyors, Sri Lanka Hony, Treasurer						
Please Return This Part with your payment						
CREDIT CARD / CHEQUE PAYMENT SLIP						
CHEQUE VISA MASTER Cheque # Cheque Date/						
_	CREDIT CARD DETAILS Name as appeared in the Card					
	Card No. Expiry Date mm yyyy					

CHEQUE VISA MASTER	Cheque #	Cheque Date//			
CREDIT CARD DETAILS Name as appeared in the Card					
Card No.		Expiry Date mm yyyyy			
	S[S]				
CONTACT DETAILS Telephone: 1	Email Address:				
I hereby authorize the use of my credit card to debit the amount mentioned above:					
•					
CARD HOLDER'S SIGNATURE		DATE			
Change of Address:					
	Mail to: INSTITU	JTE OF QUANTITY SURVEYORS SRI			
	The Professional				
	Colombo 07.	5/75, Prof. Stanley Wijesundara Mawatha			
	E-mail : Scan the	form and e-mail to: <u>iqssl@sltnet.lk</u>			

* Note: CVV #, is the three (03) digits, printed on back of the Credit





www.iqssl.lk